



THE NEXT GENERATION OF MASTER KEY CONTROL



Introducing **KNOX KEYSECURE® 6**

Engineered to provide the highest level of flexibility, security and accountability, the Knox KeySecure 6 is the next generation of master key control. With options for dual support of a Knox mechanical master key and the new electronic key, Knox eKey™, the KeySecure 6 provides flexibility and investment protection enabling your rapid access system to evolve into the next generation of rapid access: the Knox eLock System™.

The KeySecure 6 utilizes KnoxConnect™, a cloud-based management system, to disable eKeys, authorize users, configure devices, and retrieve audit trail information from any device connected to the web.



Flexibility

Configurable to secure both a mechanical key and eKey, making the transition to the electronic system easy.



Security

Knox mechanical master key and Knox eKey are securely locked and only accessible using a user-specific PIN code.



Accountability

Retrievable, end-to-end traceability on key usage via KnoxConnect.

COMPONENTS OF THE KEYSECURE® 6



KNOXCONNECT

Cloud-Based Management System

- Used to configure and manage the Knox eLock System devices and users
- Admins have the ability to manage users and PIN codes, retrieve audit trail events and create reports from any device via a web browser



KEYSECURE 6

Key Retention Device

- Key control device used for securing, programming and charging the Knox eKey along with an option to secure a Knox mechanical master key
- Utilizes individualized PIN codes to release keys



MOUNTING BRACKET

60°, 90°, Flat Mount Options

- Mounts securely in an apparatus, vehicle, or office
- Optional mounting brackets available in flat, 60 and 90 degrees

KEYSECURE 6 PRODUCT SPECIFICATIONS*

Construction	Die-cast zinc
Dimensions	6.0" H x 4-1/4" W x 3-1/2" D
Product with WiFi Antenna	WiFi antenna extends an additional 1-1/2" from side of unit and adds up to 4-1/4" above the unit when oriented upward
Weight	7.8 lbs (shipping weight)
Finish	Powder coating
Key Carrying Capability	1 Knox eKey or 1 Knox eKey and 1 Knox mechanical master key
Operating Temperature	-20° to 60° C
Storage Temperature	-40° to +80° C
Alert LEDs	Yes (2)
Power	Vehicle 7-amp 12-volt DC power supply or AC adapter
Initial Power Stabilization Time	Up to 5 seconds
Audit Trail Events	Up to 16,000 events
User PIN Codes	Up to 5,000

Model #	Type
KS-6K1	KeySecure 6 unit only, secures eKey only
KS-6K2	KeySecure 6 unit only, secures both an eKey and a mechanical key
KS-6K1-B	KeySecure 6 bundle package, secures and includes 1 eKey and mounting bracket
KS-6K2-B	KeySecure 6 bundle package, secures both an eKey and a mechanical key; includes 1 eKey and mounting bracket

* Models and specifications subject to change without notice.

Contact your Regional Account Manager for more information.

knoxbox.com | 800-552-5669