

RAISING THE BAR ON SECURITY & SUPPORT

KNOX KEYSECURE[®] 5

Knox master key control is elevated with new security and support capabilities. The KeySecure 5 device leverages Knox technology to provide secure, rapid access when seconds matter.

KeySecure 5 features dual key security and KnoxConnect[™], a cloud-based management system, to configure devices, manage users, track access and review audit trails for accountability.

 \mathcal{L}^{O}

Flexibility

The KeySecure 5 holds up to two keys, providing departments the ability to secure and support shared systems.



Security

Knox Master Keys are securely locked and only accessible with a userspecific PIN code. All access activity is tracked through KnoxConnect.

<u>_</u>	
[~—]	l
×—	
[⁰ —]	N

1 2 3 4 5 6 7 8 9 0

Accountability

Tracking user access by name, date and time, the KnoxConnect maintains accountability and integrity of the system.

knoxbox.com | 800-552-5669

COMPONENTS OF THE KEYSECURE[®] 5



KNOXCONNECT

Cloud-Based Management System

- A cloud-based system used to configure, program and manage the key control devices
- Admins have the ability to assign PIN codes, add/delete users, and create reports from any web-enabled device with a browser



KEYSECURE 5

Key Retention Device

- Secures up to two Knox Master Keys and a Knox Keywrench
- Releases key(s) with a secure, individualized PIN code



MOUNTING BRACKET

60°, 90°, Flat Mount Options

- Mounts securely in an apparatus, vehicle, or office
- Optional mounting brackets available in flat, 60 and 90 degrees

KEYSECURE 5 PRODUCT SPECIFICATIONS^{*}

Construction	Die-cast zinc
Dimensions	6.0" H x 4-1/4" W x 3-1/2" D (KSM-200)
Product with WiFi Antenna	WiFi antenna extends an additional 1-1/2" from side of unit and adds up to 4-1/4" above the unit when oriented upward
Weight	8.0 lbs (shipping weight)
Finish	Powder coating
Key Carrying Capability	1 or 2 mechanical keys
Operating Temperature	-20° to 60° C
Storage Temperature	-40° to +80°C
Alert LEDs	Yes (2)
Power	Vehicle 7-amp 12-volt DC power supply or AC adapter 7-amp 12-volt
Initial Power Stabilization Time	Up to 5 seconds
Audit Trail Events	Up to 16,000 events
User PIN Codes	Up to 5,000

* Specifications subject to change without notice.