

KNOX STANDPIPE LOCK®

The Knox Standpipe Lock® protects standpipes and hydrant hose connections from accidental damage, vandalism, and physical attack. Since the Knox Standpipe Lock holds water pressure, it can be installed on hydrants to help prevent water theft. The Knox Standpipe Lock is available for 2.5" to 3" connections with varying thread options and is operated with a Knox FDC Wrench controlled by the Fire Department.



FEATURES

- Standard threads are NH (3.068 X 7.5TPI) but can be customized to fit any 2.5" to 3" thread pattern
- ✓ Water-tight to pressures exceeding 700 psi
- → Heavy-duty stainless steel construction to resist physical attack
- ✓ Stainless steel locking mechanism
- ✓ Brass threads
- Authorized by 2018 IFC and IBC (Chapter 905.11)

BENEFITS

- ✓ Protects dry and wet standpipe outlets in stairwells from vandalism
- ▼ Reduces unauthorized cap removal and cap theft
- Assures uncompromised threads
- ✓ Discourages water theft

APPLICATIONS

- Wet and dry standpipes
- Fire hydrants
- ✓ Wall hydrants

ORDERING SPECIFICATIONS

To insure procurement and delivery of the Knox Standpipe Lock, it is suggested that the following specification paragraph be used:

Knox Standpipe Lock made of stainless steel.

Size: 2.5-inch or 3-inch

Construction: Stainless steel with brass threads **Lock:** Locks with a proprietary Knox FDC Wrench

P/N: Use the corresponding part # listed on the following page

Mfr's Name: KNOX COMPANY

ABOUT THE KNOX COMPANY

Since 1975, the Knox Company has successfully developed innovative rapid access solutions for first responders with products that provide fast, safe, and secure entry into commercial, industrial, and residential properties, while minimizing damage and maximizing safety. Today, more than 15,000 fire, EMS, and law enforcement departments/agencies depend on Knox products to gain access into over one million buildings/properties.

WARNING:

This product can ONLY be installed when authorized by the local fire department jurisdiction. This is a security product that requires the universal Knox FDC Wrench to lock the cap in place.



KNOX STANDPIPE LOCK®

KNOX STANDPIPE LOCKS ARE AVAILABLE IN THESE THREAD SIZES	
2.5"	Model
2.841 X 8.0 TPI	4031
2.990 X 7.5 TPI	4029
3.000 X 8.0 TPI	4013
3.058 X 6.0 TPI	4017
3.062 X 6.0 TPI	4015
3.068 X 7.5 TPI (NH/NST)	4011
3.078 X 6.0 TPI	4027
3.078 X 7.0 TPI	4033
3.078 X 8.0 TPI	4019
3.110 X 8.0 TPI	4041
3.112 X 8.0 TPI	4039
3.125 X 7.5 TPI	4037
3.142 X 7.0 TPI	4021
3.187 X 6.0 TPI	4023
3.218 X 6.0 TPI	4025
3.234 X 6.0 TPI	4045
3.252 X 6.0 TPI	4035
TEST HEADER CAP	4044
<u>3"</u>	
3.623 x 6.0 TPI (3" NH/NST-San Francisco)	4047

Knox FDC Locking Caps are available in a variety of thread sizes. If your specification is not listed, send an email to info@KnoxBox.com to inquire about additional options.

